

Data sheet

valid from: 4/7/26





Variable area flow meter type 335
Float in PVDF without magnet
With PP-H butt fusion spigots IR

Model:

- Standard guiding rod PVDF with stainless steel core (V4A) for DN50 and DN65

Option:

- 4-20 mA sensor
- Limit contacts
- Special scales for different media
- Union nuts and connecting parts in other materials on request

Scale range (l/h)	d (mm)	DN (mm)	Taper tube in PVC-U transp. Orings in EPDM Code	SP	Weight (kg)	D (mm)	L (mm)	L1 (mm)	L2 (mm)
50 - 500	32	25	**800 046 010**	1	0.480	58	453	341	335
100 - 1000	32	25	**800 046 011**	1	0.508	58	453	341	335
150 - 1500	40	32	**800 046 012**	1	0.620	72	461	341	335
250 - 2500	40	32	**800 046 013**	1	0.610	72	461	341	335
200 - 2000	50	40	**800 046 014**	1	0.900	83	465	341	335
300 - 3000	50	40	**800 046 015**	1	0.900	83	465	341	335
600 - 6000	50	40	**800 046 016**	1	0.900	83	465	341	335
600 - 6000	63	50	**800 046 017**	1	1.225	101	472	341	335
1000 - 10000	63	50	**800 046 018**	1	1.225	101	472	341	335
1500 - 15000	63	50	**800 046 019**	1	1.225	101	472	341	335
2000 - 20000	75	65	**800 046 020**	1	2.150	135	495	341	335
3000 - 30000	75	65	**800 046 021**	1	2.150	135	495	341	335
8000 - 60000	75	65	**800 046 022**	1	2.150	135	495	341	335

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com