
Data sheet

valid from: 8/27/26





Special version Type 335 PVDF-HP
Float in PVDF (white) without magnet
With fusion spigots BCF/IR
O-rings in FKM (white)

d (mm)	DN (mm)	Size (inch)	Scale range (l/h)	Scale range (gal/min)	Polysulfone Code	Weight (kg)	D (mm)	L (mm)	L2 (mm)	G (inch)
32	25	1	100 - 1000	0.4 - 4.4	**198 335 160**	0.401	60	453	335	1 ½
50	40	1 ½	300 - 3000	1.3 - 13.2	**198 335 161**	1.030	83	466	335	2 ¼
50	40	1 ½	600 - 6000	2.6 - 26.4	**198 335 162**	0.978	83	466	335	2 ¼
63	50	2	1000 - 8000	4.4 - 35.2	**198 335 163**	1.500	103	472	335	2 ¾
63	50	2	1500 - 15000	6.6 - 66.0	**198 335 164**	1.500	103	472	335	2 ¾
75	65	2 ½	2000 - 20000	8.8 - 88.0	**198 335 165**	2.500	122	495	335	3 ½
75	65	2 ½	3000 - 29000	13.2 - 127.7	**198 335 166**	2.500	122	495	335	3 ½

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com